

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number
WO 2004/002200 A1

(51) International Patent Classification⁷: **H05B 41/292**

PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(21) International Application Number:

PCT/IB2003/002764

(72) Inventors; and

(22) International Filing Date: 16 June 2003 (16.06.2003)

(75) Inventors/Applicants (*for US only*): **MÖNCH, Holger** [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weiss hausstr. 2, 52066 Aachen (DE). **RIEDERER, Xaver** [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weiss hausstr. 2, 52066 Aachen (DE). **DEPPE, Carsten** [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weiss hausstr. 2, 52066 Aachen (DE). **LÜRKENS, Peter** [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weiss hausstr. 2, 52066 Aachen (DE).

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

02014172.7 25 June 2002 (25.06.2002) EP


(74) Agent: **MEYER, Michael**; Philips Intellectual Property & Standards GmbH, Weiss hausstr. 2, 52066 Aachen (DE).

(71) Applicant (*for DE only*): **PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH [DE/DE]**; Stein-damm 94, 20099 Hamburg (DE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, IT, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MC, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SZ, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW only): **KONINKLIJKE**

[Continued on next page]

(54) Title: OPERATION OF A DISCHARGE LAMP



(57) Abstract: The invention relates to a method for operating a discharge lamp 11 including two electrodes 12,13. The method comprises applying to the electrodes an alternating current I_{Lamp} . In order to improve the performance of the lamp and to increase the life time of the lamp, it is proposed that the alternating current has a direct current component DC for compensating a temperature difference between the two electrodes. The direct current component is selected more specifically such that a first electrode, which is expected to have a lower temperature than the second electrode, functions as anode for the direct current component, while the second electrode functions as cathode for the direct current component. The invention relates equally to an electronic circuit and to a software program for operating a discharge lamp correspondingly, as well as to a lighting system comprising a discharge lamp and means for operating this discharge lamp correspondingly.